



life without limit™

installation instructions

urban jungle™ universal travel system



For any assistance, please contact your nearest retailer listed at
www.mountainbuggy.com

Model MB1-CLIP1
Issue August 2009

Safety certified: ASTM F833-08
EN 1888:2005
AS/NZS 2088:2000



send 102-112 Daniell St, Newtown 6021, Wellington, New Zealand
ph +64 4 380 0833
fax +64 4 380 0137

Designed in New Zealand. Made in China.

WARNINGS

Check you have the correct travel system for your carseat.

WARNINGS

Do not use this travel system until you have read and understood the instructions!

WARNINGS

Never leave your child unattended.

WARNINGS

Do not use accessories not designed for your buggy as they may be unsafe.

WARNINGS

Do not leave your baby in carseat (on or off stroller) for long periods of time.

IMPORTANT CHECKS

- Make sure baby is harnessed into carseat using the manufacturer's instructions.
- When fitting carseat onto travel system, ALWAYS keep a steady hand on carseat and baby.
- Check travel system is engaged correctly onto buggy frame and cannot move in any direction. (Refer back to installation instructions to ensure positioning of snap locks are correct).
- Do not use travel system if you are unable to secure carseat or travel system. In this case, contact your store/distributor where the buggy was purchased from, for more help.
- It is recommended that you practise the following instructions without baby in carseat.


PREPARING THE BUGGY

⚠ WARNINGS

ALWAYS put the buggy brake on.


Note: the sunhood and seat need to be removed from buggy before fitting travel system.

1. Temporarily remove sunhood.
2. Unfasten seat from frame along side tubes, including straps at point A & B on both sides of buggy, and strap underneath seat at point C.
3. Remove seat.





FITTING TRAVEL SYSTEM TO BUGGY

1. Attach the fasteners on travel system fabric to fasteners on buggy frame at points A, B, C & D.
2. Fasteners at A & B are above sunhood lug. Fasteners C & D are below hinge joint.





FITTING TRAVEL SYSTEM TO BUGGY (continued)

3. Ensure fabric passes over and around frame tubes.
4. Open snap locks and press travel system onto frame directly above bottom fasteners on side tubes.
5. Close both snap locks down flat, making sure you hear the lock "click" indicating they are fully locked.



FITTING CARSEAT ONTO TRAVEL SYSTEM

1. Place carseat in travel system so that baby faces buggy handle bar.
2. Pass wide straps around frame directly below sunhood lugs and through slots provided on each side of carseat. (the slots are the same as used for carseat belt).
3. Buckle wide strap across top of carseat at point Z and tighten firmly by pulling on free end of strap.



REMOVE CARSEAT FROM TRAVEL SYSTEM

1. Unbuckle travel system buckle and remove straps from slots on carseat.
2. Lift carseat off travel system.

REMOVE TRAVEL SYSTEM FROM BUGGY

1. Open two snap locks and take snap locks off frame tube.
2. Unfasten four fasteners on frame and lift travel system off buggy.